



ENDUTEX - REVESTIMENTOS TEXTEIS, SA

VIZELA / PORTUGAL



TECHNICAL DATA SHEET

REFERENCE: POLYCRIL 200 FR

DESCRIPTION : RESIN COATED POLYESTER WOVEN FABRIC

COMPOSITION : 22 % RESIN
78 % POLYESTER

WIDTH : Up to 320 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.31	
TOTAL MASS (g/m ²)	200 ± 20	EN ISO 2286-2
FABRIC MASS (g/m ²)	155 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 130 T.: 100	EN ISO 1421
BREAKING EXTENSION (%)	L.: 25 T.: 25	EN ISO 1421
TEAR STRENGTH (daN)	L.: 3.0 T.: 5.0	EN ISO 4674-1B
BURNING BEHAVIOUR	B1	DIN 4102

L - Along T - Across

NOTE : Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2009.07.31	0		